

3W6 SWAMP BUGGY

COMBINING TECHNOLOGY AND TRADITION SINCE 1976



Light Weight and High Flotation

GK's 3W6 Swamp Buggy is the top choice for a quality, long-lasting and low maintenance machine. The 3W6 is more maneuverable and adaptable than other buggy's on the market today and is a great choice for light weight, high-flotation applications for both spreading and spraying.

- 3-wheel stance to provide staggered tire track spacing
- Light weight to limit ground pressure and compaction
- Adaptable and interchangeable for liquid and dry application systems
- Can be configured with Tundra flotation or row crop tires

New and Improved Features:

- New optional wide cab with more tinted-glass area than any other cab on the market; increased visibility and improved noise reduction
- New optional wide cab also comes with a training seat
- New stereo system with Bluetooth, weather-band and hands free calling
- Air-seat is now standard in the 3W6 for both regular and large cabs
- 600 gallon tank with new large optional rinse tank

The 3W6 is powered by a 6-cylinder (173 horse power) Cummins diesel engine which provides 590 foot-pounds of torque. It's delivered through an Allison 4-speed automatic transmission, driven by an outboard planetary rear-end, single speed with internal wet brakes. The main frame chassis features a wheel base of 15' 6" and offers 6,000 lbs. payload capacity. It has a dry weight of 11,000 lbs.

This versatile machine spray system is designed with a 600 gallon stainless steel tank with mechanical agitation, 60' 70' or 80' stainless booms and a centrifugal or diaphragm pump. Spreading systems can be designed with either 2 or 3 ton stainless dry-box with double spinners.



Call for a friendly quote!

503-678-5525

10590 Donald Road NE · Donald, Oregon 97020 FAX 503-678-5693 gksales@gkmachine.com · www.gkmachine.com

3W6 SWAMP BUGGY

COMBINING TECHNOLOGY AND TRADITION SINCE 1976



SPECIFICATIONS:

- ENGINE** Cummins 6-cylinder, 173 HP
- CAB** Pressurized cabin with sound insulation
Charcoal air filtration system
Climate control (A/C, heat, defrost)
AM/FM stereo CD player Comprehensive digital display cluster
- SPRAY PUMP** Centrifugal Hypro HM1 or HM4
- FRAME** 15' 6" wheel base with 6,000 lbs. payload
Dry weight of 11,000 lbs. with spray tank
- TRANSMISSION** 4-speed automatic Allison AT545
- REAR AXLE** Outboard planetary, single speed with internal wet brake

OPTIONAL PERFORMANCE FEATURES:

- SPRAY BOOM** 60, 70 or 80 feet suspended boom with stainless steel wings
- TIRE OPTIONS** Tundra tire and wheels (66 x 44 x 25)
Row crop 12.4 R46 radials
- LIQUID SYSTEMS** 600 gallon stainless steel tank
- OTHER OPTIONS** Durafoam – foaming system, 10 or 20 gallon capacity
Raven precision components
Dual spinner dry-box, 2 or 3 ton
New Stainless steel wide cab



Call for a friendly quote!

503-678-5525

10590 Donald Road NE · Donald, Oregon 97020 FAX 503-678-5693 gksales@gkmachine.com · www.gkmachine.com