

TH2 HIGH CLEARANCE SPRAYER

COMBINING TECHNOLOGY
AND TRADITION SINCE 1976



Over the Top Performance

Massive height clearance and width adjustability, this tracked power unit offers a versatile machine to handle a variety of crops, vineyards and nurseries. The TH2 covers fields fast and efficiently with the following performance features:

- The 16" wide rubber tracks adjust to 88 to 132 inches in width, extending the tracks to a staggering 144 inches in length.
- A low center of gravity, weight is distributed to allow the TH2 to sit comfortably on steep hillsides and uneven terrain.
- It's low impact ground pressure lessens operator damage to plant roots, offers less soil compaction and the ability to operate in moist conditions.

From wet drops and broadcast spray systems to granular fertilizer spreaders, the TH2 is customizable to your crop needs. Options of additional attachments including pre-pruners, hedgers and trimmers, flail and rotary mowers all easily mount to the machine frame.

The TH2 is powered with a John Deer 4-cylinder 173 HP diesel engine. Transferring power hydrostatically to two independent carriage drive motors, as well as optional auxiliary drives for attachments, the TH2 also offers a hydraulically censored track tensioning control system.



The TH2 is designed to fit perfectly inside
a standard steel shipping crate for easy
international shipping



TH2 HIGH CLEARANCE SPRAYER

COMBINING TECHNOLOGY
AND TRADITION SINCE 1976



SPECIFICATIONS

Engine	John Deere 4-cylinder 173 HP
Ground Clearance	Tunnel clearance 108"
Width Adjustment	Track width adjustable on-the-go (88" to 132" or 96" to 144")
Cab	Pressurized cabin Charcoal air filtration system Climate control (A/C, heat) AM/FM stereo CD player Comprehensive gauge cluster on digital display unit
Rubber Tracks	Positive nonslip drive system • 16" wide tracks
Hydraulic Systems	30 gal. minute load sense High-pressure circuit and 15 GPM low pressure circuit on each side
Ground Pressure	4.5 to 6.5 PSI
Spray System	Hypro HM1 or HM4 centrifugal pump 300 gallon poly tank Unique Air-blast full coverage spray configuration available

OPTIONAL PERFORMANCE FEATURES

Engine	John Deere 4-cylinder 115 HP
Hydraulics	3-point hitch and PTO Front and/or rear category II 3-points with 1200 lbs. lift capacity
Implements	Pre-pruners and trimmers • Hedgers • Flail and rotary mowers • Custom implements
Spray System	Broadcast boom • Drop boom sections • Hypro-centrifugal or diaphragm spray pump Spray booms in a variety of sizes • Raven spray controller • In-cab joystick controller Pressurized wet drops • Air assist systems • Fertilizer spreaders
Rubber Tracks	12" narrow gauge tracks

