

TR6 TRACKER

COMBINING TECHNOLOGY
AND TRADITION SINCE 1976



High, Wide and Low Impact

Ideal for farm operators and custom applicators, the TR6 Tracker solves your height and width issues:

- The TR6 has the size, the power, the capacity and overall productivity to cover big acreages fast and efficiently.
- Designed to straddle multiple crop rows while carrying large capacity of product, the TR6 has a towering stance and “on-the-go” track width and height adjustment.
- Its low impact ground pressure allows operation in adverse ground conditions.

The TR6 efficiently operates as an over the row spray delivery system with 400 gallon capacity and mechanical agitation, centrifugal or diaphragm pumps, product controllers, and a variety of boom configurations and sizes.

From wet drops and broadcast booms to air blast systems and granular fertilizers spreads, the TR6 is customizable to your specific crop needs. Options of front or rear mounted 3-point hitches offer the use of additional attachments including pre-pruners, hedgers, flail mowers, trimmers and many other implements – they easily mount on the machine frame.

GK Machine custom builds each spray system to each customer’s exact needs and specifications. Our goal is to make your operation more efficient, saving you time and money.



TR6 TRACKER

COMBINING TECHNOLOGY
AND TRADITION SINCE 1976



SPECIFICATIONS

Engine	Cummins 6-cylinder 6.7L, Tier III, 173 HP
Ground Clearance	Adjustable: 77" to 87" or 77" to 97"
Width Adjustment	Track width Adjustable on-the-go (80" - 120" or 96"-136")
Cab	Pressurized cabin with sound insulation • Charcoal Air Filtration System Climate Control (A/C, Heat, Defrost) • AM/FM stereo CD player Comprehensive Digital Display Unit
Rubber Tracks	Positive nonslip drive system • Unique bogey track rollers
Hydraulic Systems	Sundstrand • Heavy-duty hydrostatic drive
Steering	Tilt/telescopic steering column • Electronic steering with adjustable sensitivity Capable of zero radius spot turns
Ground Pressure	5.5 to 7.5 PSI

OPTIONAL PERFORMANCE FEATURES

Engine	Cummins 6-cylinder 200 HP, 6.7 L, Tier III
Hydraulics	3-point hitch and PTO Front and/or rear category II 3-points with 120 lbs. lift capacity 65 HP hydraulic PTO 30 GPM
Implements	Pre-pruners Hedgers Flail Mowers Custom Implements
Spray System	Hypro-centrifugal or diaphragm spray pump Spray booms in a variety of sizes Raven spray controller In-cab joystick controller Pressurized wet drops Broadcast booms Air Assist Systems Fertilizer Spreaders

